

# Product Data Sheet

## VISCOTAQ® EZ-Wrap



### Product description

VISCOTAQ® EZ-WRAP is a non-crystalline, a-polar viscous elastic solid polyolefin coating in roll form that is a versatile and economical product intended for corrosion protection and waterproofing of a wide range of applications for above-ground substrates. The EZ-Wrap is commonly applied as a system in conjunction with and for protection of the VISCOTAQ® ViscoSealant.

VISCOTAQ® EZ Wrap provides a quick and economical method of installation with excellent sealing properties. VISCOTAQ® EZ Wrap has a polyester, reinforced fiber top layer that allows for the immediate painting or coating after installation. EZ Wrap is applied by removing a release liner and applying the tacky side to a clean and dry substrate. VISCOTAQ® EZ Wrap can be used in environments and on substrates with an ambient or surface temperature up to +71°C/+160°F. The product can be applied without significant surface preparation. The EZ-Wrap is engineered to prevent water infiltration in a variety of industries such as telecommunications, utilities, transportation, electrical, water and wastewater, agriculture and more. Applications consist of sealing tank chimes, flanges, vaults penetrations, metal roof seams, around rooftop vent pipes, pipes, flashing, EPM roofing, cable entries, holes, cracks, storage tanks, industrial pools, manholes, basements, cable joints and more.

### Performance

VISCOTAQ® EZ-Wrap is a long-term solution to a variety of water infiltration problems. VISCOTAQ® EZ-Wrap has been installed with success on a variety of substrates in numerous environments to prevent water infiltration. Consult Amcorr Products & Services for additional project information.

### Specifications

VISCOTAQ® EZ-Wrap is a mastic-like material designed with synthetic properties that will adhere to almost any surface without a primer. VISCOTAQ® EZ-Wrap comes in rolls and is designed to be used as a long-term solution for water infiltration and corrosion prevention.

### Physical Properties

- Product Name: VISCOTAQ® EZ-Wrap
- Compound color: Blue
- Odor: None
- Adheres to Wet Surface: No
- Material Phase: Solid
- Shelf Life: Unlimited
- Maximum Operating Temp: +71°C/+160°F

Measurement	Value	Method
Glass Transition Temperature	-42.92°C/-45.26°F	ASTM E1356-03
Material State	Solid	NA
Density	1.1-1.3	DIN 53479
Water Vapor Permeability	<4 *10 <sup>-4</sup> g/day/m <sup>2</sup> /Pa	ASTM E96/96M-10
Water Absorption	<0,03%	ISO 62
Electric Resistance	>10 <sup>12</sup> ohm/cm	ASTM D257

For additional information, please contact:  
Amcorr Products & Services, Inc.  
p. 210-514-1091  
[www.amcorrusa.com](http://www.amcorrusa.com)  
[ewelles@amcorrusa.com](mailto:ewelles@amcorrusa.com)

