

<i>Only minimal surface preparation is required</i>	<i>Easily conforms to irregular surfaces</i>	<i>No curing time needed for immediate service fillers</i>	<i>Environmentally safe, non toxic, no VOC's</i>	<i>Will not dry out in heavy clay soils</i>	<i>Applied over wet or dry surfaces</i>
-----------------------------------------------------	----------------------------------------------	------------------------------------------------------------	--------------------------------------------------	---------------------------------------------	-----------------------------------------

SCC Pro Mold Putty Excellent for molding irregular surface for an even application of SCC's Wax Wrap.



Description:

Petroleum based anticorrosive filling compound that provides the ability to mold irregular surfaces for an even application of SCC's Wax Wrap

Application Procedures:

Application Procedure: To prepare the surface remove all loose scale, rust, paint, and other foreign material. By hand, apply SCC Pro Mold Putty to the surface. Press and mold the material onto the surface ensuring the putty is wetting and adhering. Continue working SCC Pro Mold Putty to the area until desired profile is achieved. Once desired profile is achieved, finish by overwrapping with SCC's Wax Wraps.

Technical Data:

<i>Properties</i>	<i>English</i>
Color	Gray
Specific Gravity	1.11
Maximum Service Temperature	200°F
Flash Point	>350°F

Packaging

2 gallon pail	Sold Individually
---------------	-------------------