



SCC WAX WRAP 80U BELOW-GROUND

An 80-90mil, petroleum based compound impregnated into a non-woven synthetic carrier that provides long-term corrosion prevention.

USE:

For application on **below-ground** metal structures and pipelines needing corrosion protection.

PACKAGING:

4"x9' rolls (24 Rolls/Case)	Coverage:	72ft ²	50% Overlap: 36ft ²
6"x9' rolls (16 Rolls/Case)	Coverage:	72ft ²	50% Overlap: 36ft ²
9"x18' rolls(6 Rolls/Case)	Coverage:	81ft ²	50% Overlap: 40ft ²
12"x18' rolls(4 rolls/Case)	Coverage:	72ft ²	50% Overlap: 36ft ²

*Other widths, lengths **and** 60 mil available

SPECIFICATIONS:

Color	Brown
Thickness	80-90mils
Dielectric strength	296 volts/mil
Cathodic Disbonding	Resistance(ASTM G-8) Zero Disbondment
Moisture Vapor Rate	Permeability Rate ASTM E96 0.00024 perms avg.
Application Temperature	0°F to 155°F
Operating Temperature	-50°F to 155°F
Drop Melt Point(ASTM D127)	179°F
Cone Penetration(ASTM D937)	6.4
Flash Point(ASTM D92)	538°F

ADVANTAGES:

- SP-2, only minimal surface prep required
- Ideal when transitioning from old coating
- Superior in extreme environments
- No cure time, immediate backfill
- Nontoxic, no VOCs
- No Clay Fillers
- Easily conforms to irregular shaped surfaces
- CP Compatible
- Meets and Complies with AWWA C217 Standard, NACESP0375-2018