

TECHNICAL DATA SHEET

PrimeGuard Primers

UNDER SCC WAX WRAP

Surface conditioners that displace moisture and prepare the substrate prior to application of the SCC Wax Wrap, for above-ground, below-ground and marine applications.

PRIMEGUARD PRIMER



DESCRIPTION

PrimeGuard is a formulation of petroleum-based waxes, plasticizers, and moisture-displacing compounds. Designed to be applied to dry or wet surfaces.

PrimeGuard conditions the surface by displacing moisture and creating a corrosion-inhibiting interface for the application of SCC Wax Wrap. PrimeGuard is offered in above-ground and below-ground grades.

SPECIFICATIONS

Color	Brown, White
Coverage	1 gal / 100 ft ²
Flash point	507°F
Drop melt point	176°F
Operating temperature	-50°F to 155°F
Application temperature	0°F and above

PRIMEGUARD 250



DESCRIPTION

PrimeGuard 250 is a formulation of petroleum-based waxes, plasticizers, and moisture-displacing compounds.

PrimeGuard 250 is formulated to be used as a surface conditioner for above-ground, below-ground and marine applications, and where one might encounter high ambient temperatures and hot surfaces.

SPECIFICATIONS

Color	Brown
Coverage	1 gal / 100 ft ²
Flash point	507°F
Drop melt point	300°F
Operating temperature	-50°F to 250°F
Application temperature	0°F and above

PACKAGING 4 × 1 gallon pails per case · both grades